



SERIES 750 CASEMENT WINDOW



Series 755 awning window also available

STANDARD FEATURES

- Beautiful beveled exterior frame perimeter
- Low profile handle folds in and provides a popular aesthetic appeal
- Narrow profile permits expanded viewing area
- Fusion-welded frame and sash for weather-tight performance
- Full-perimeter double weather stripping
- Pre-punched nail fin makes installation simple
- Insulated glass panels featuring warm-edge spacer system
- Concealed hinges and hardware let you open casement windows 90 degrees for better ventilation and easier cleaning
- Full screens* mount on the interior and are removable for easy cleaning
- Tandem locks come standard on all casements over 34" in height
- Jamb depth: 3.25"
- Multi-point locking system provides superior pull-in mechanism with single lever
- **Limited lifetime warranty**



Single vent casement

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance and 1/8" simulated divided lite (SDL) grids
- 2" simulated meeting rail
- 8 painted exterior colors (white interior only)
- Charcoal aluminum, Clear View and heavy duty screens*



Sleek folding handle



Brick mould exterior



Pre-punched nail fin




Attractive beveled edge adds classic charm



Single vent awning



ENERGY STAR compliance available in all series. Verify product specifics before ordering.



Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.
 * Screens are not meant to restrain a child from falling through an open window.
 ** Printing process may affect color shown. Please refer to actual window sample when selecting colors.
 *** Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

