



# SERIES 85 ALUMINUM NON-TILT SINGLE HUNG WINDOW

Also available in 2- and 3-lite sliders and picture windows


## STANDARD FEATURES

- Aluminum frame and sash components are precision cut and assembled to make joints weather-tight
- Warm-edge insulated glass reduces condensation and improves thermal efficiency
- Sashes interlock for added strength and security
- Weather stripping at interlock and sash stile helps block air and water infiltration
- Positive sash lock provides security and helps keep the frame and sash weather-tight
- Half screen standard\*
- Full perimeter weather-strip insulation provides energy saving thermal efficiency
- 9/16" insulating glass boosts thermal performance
- Vinyl bulb seal spans bottom of operable sash to minimize air and water infiltration
- Continuous extruded nail-fin on all frame sections for fast, easy installation
- 1" nail-fin setback for brick veneer construction and selected stucco applications
- Sloped-sill allows for easy water run-off
- DP-40 Rating (window size tested 48" x 84")
- Jamb depth: 2.5625"
- **Limited lifetime warranty**

## CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 3/4" flat grids
- Custom sizes available
- DP-50 Rating (window size tested 48" x 72")

COLOR  
OPTIONS\*\*



ENERGY STAR compliance available in all series. Verify product specifics before ordering.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.

\* Screens are not meant to restrain a child from falling through an open window.

\*\* Printing process may affect color shown. Please refer to actual window sample when selecting colors.