



# REPLACEMENT DOUBLE HUNG WINDOW FEATURE COMPARISON

## Universal Standard Features of the Series 3201, 3500 and 3900 Double Hung Windows

- Virtually maintenance free, premium vinyl construction
- All-welded 45° frame and sash corners
- 3 1/4" jamb depth
- 3/4" insulated glass with Intercept Sealant System
- Dual, push button night vents
- Low profile tilt latches
- Dual zinc plated pivot pins
- Dual safe-slip locking balance shoes
- Full width extruded interlock at meeting rail
- Dual deluxe cam locks (widths 27 1/4" or greater)
- Sloped sill design for easy water run-off



- Head expander and sill angle
- Beveled exterior profile
- Multi-cavity frame construction
- Dual fin weather stripping
- Slimline, continuous lift rail at top and bottom sashes
- Individually registered warranty ID label
- Transferable, limited lifetime warranty

## Additional Features

GLASS	SERIES 3201	SERIES 3500	SERIES 3900
Low-E Glass	Optional	Optional	Optional
Low-E Glass with Argon Gas	Optional	Optional	Optional
Ultra Low-E Glass with Argon Gas	Optional	Optional	Optional
Tempered Glass	Optional	Optional	Optional
Obscure Glass	Optional	Optional	Optional
Double Strength Glass	Optional	Optional	Optional
SCREEN			
Extruded Half	Standard	Standard	Standard
Extruded Full	Optional	Optional	Optional
GRID			
5/8" Flat	Optional	Optional	Optional
5/8" Contoured	Optional	Optional	Optional
3/4" Flat	Optional	Optional	Optional
1" Contoured	Optional	Optional	Optional
Diamond Grid Pattern	Optional	Optional	Optional
1 1/8" Simulated Divided Lite (SDL)	N/A	Optional	Optional





# REPLACEMENT DOUBLE HUNG WINDOW SPECIFICATIONS AND OPTIONS



Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.



GLASS	SERIES 3201	SERIES 3500	SERIES 3900
Design Pressure	DP-35	DP-35 (DP-50 Optional)	DP-60
Vinyl Weight (36" x 60")	16.375 lbs.	18.00 lbs.	21.813 lbs.
Frame Width	3.5625"	3.67"	4.25"
Glass Breakage Warranty	N/A (Lifetime Optional)	25 years (Lifetime Optional)	Lifetime (Standard)
Balance System	1/2" Coil Balance	1/2" Coil Balance	3/4" Coil Balance
Interior Frame Face	1 1/2"	1 3/8"	1 5/8"
Sash Stile Thickness	0.062"	0.065"	.065"
External Accessory Groove	N/A	N/A	Standard
Insulated Glass Warranty Protection	15-30 Years	25 Years to Lifetime	All-Inclusive Lifetime
Nine Exterior Painted Colors (white interior only)	Optional	N/A	Optional
Bronze Exterior Laminate	N/A	Optional	N/A
Window Opening Control Device (WOCD)	Optional	Optional	Optional

## Series 3900 Exclusive Options:

- Triple pane, R-5 compliant glass with Super Spacer® sealant system (two options)
- InsulKor™ multi-cavity foam-filled frame injections
- Nine exterior painted colors\*\*\* (white interior only)
- Nail fin add-on for remodeling or new construction projects



Black



Hunter Green



Clay



Dark Chocolate



Brick Red



Gray



Tan



Terratone



Bronze

\*\* Printing process may affect color shown. Please refer to actual window sample when selecting colors.  
\*\*\* Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

