



SERIES 105 HORIZONTAL SLIDING WINDOW

Also available in Series 3050 without nailing fin



STANDARD FEATURES

- 1 1/4" Nail-fin setback for brick veneer construction and select stucco applications
- Sweep lock helps provide a weather-tight seal and added security
- Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy saving comfort inside
- Versatile half screen* installs easily from inside
- Double insulated glass provides energy saving efficiency; a host of glass options are available, including Low-E coatings and Argon gas fill for additional efficiency and ENERGY STAR® compliance
- Multi-chambered vinyl lineals improve thermal performance and enhance sound absorbency
- Fusion welded frame and sash minimizes water and air infiltration and enhances overall durability
- Metal reinforced meeting rail and sash rail provide added durability and enhanced security
- Limited lifetime warranty provides reassuring peace of mind
- Pre-punched integral nail-fin targets proper nail location for quick, easy installation
- Tandem wheel and axle roller assemblies ensure smooth, easy operation on even the largest sizes
- Multi-cavity vinyl lineals improve thermal performance and enhance sound absorbency
- DP-25 Rating (window size tested 72" x 48")
- Jamb depth: 2.625"
- **Limited lifetime warranty**

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat or diamond grids
- Paintable or stainable wood jamb extensions (4 9/16" and 6 9/16")

COLOR OPTIONS**



with an 11 1/2" minimum height for use in a basement opening



ENERGY STAR compliance available in all series. Verify product specifics before ordering.

* Screens are not meant to restrain a child from falling through an open window.
** Printing process may affect color shown. Please refer to actual window sample when selecting colors.

