

SERIES 130 SINGLE HUNG WINDOW

Also available in 2- and 3-lite sliders and picture windows





STANDARD FEATURES

- Bottom sash tilts in for easv cleaning from inside
- Aluminum half screen comes standard*
- Block and tackle balance system for easy sash movement
- Warm-edge spacer system provides energy saving thermal performance
- DP-50 Rating (window size tested 53" x 77")
- Aluminum reinforcement standard in lock and meeting rails and sash stiles
- Dual Sweep locks (standard at 27 1/4" and above) help provide a weathertight seal and added security
- Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy-saving comfort inside
- Step sill design combines water run-off and aesthetic features of a sloped sill with the structural strength and internal drainage system of a pocket sill
- Jamb depth: 3"
- Limited lifetime warranty



Step Bevel design creates a beautiful exterior appearance

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- Non-reflective Low-E Glass and Non-reflective Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance, 1 1/8" Simulated Divided Lite (SDL) grids
- Nine exterior painted colors (white interior only)
- Factory mulling and factory prepared mulling
- Charcoal aluminum mesh screen*
- Obscure glass
- Double strength glass
- Oriel style
- Commodity sizing available
- Custom sizes available

































Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.





Screens are not meant to restrain a child from falling through an open window

[&]quot;Printing process may affect color shown. Please refer to actual window sample when selecting colors.
"Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.