

SERIES 130 SLIDING WINDOW

Also available in single hung and picture windows



STANDARD FEATURES

- **DP 50 RATING**
(window size tested 74" x 50" for 2-Lite and 108" x 50" for 3-Lite)
- **DP 40 Rating**
(window size tested 74" x 63" 2-Lite)
- **DP 30 Rating**
(window size tested 108" x 63" 3-Lite)
- Tandom rollers ride easily along friction free channel
- Aluminum half screen comes standard*
- Integrated glide rail for easy sash opening and closing
- Warm-Edge spacer system provides energy saving thermal performance
- Aluminum reinforcement standard in lock and meeting rails
- Dual sweep locks (standard at 27 1/4" and above) help provide a weather-tight seal and added security
- Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy-saving comfort inside
- Jamb depth: 3"
- Limited lifetime warranty



Step Bevel design creates a beautiful exterior appearance

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- Non-reflective Low-E Glass and Non-reflective Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance, 1 1/8" Simulated Divided Lite (SDL) grids
- Nine exterior painted colors (white interior only)
- Charcoal aluminum half screen*
- Obscure glass
- Double strength glass
- Commodity sizing available
- Custom sizes available

COLOR OPTIONS**



EXTERIOR LAMINATE OPTIONS** (with white interior only)



EXTERIOR PAINTED COLOR OPTIONS*** (with white interior only)



2-lite sliding window with front flange

FOUR FRAME OPTIONS:

- Front flange only
- Nail fin only (no J-channel)
- J-channel
(nail fin & front flange)
- Box frame
(no nail fin & no front flange)



* Screens are not meant to restrain a child from falling through an open window.
 ** Printing process may affect color shown. Please refer to actual window sample when selecting colors.
 *** Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.



Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.

