



SERIES 3050 HORIZONTAL SLIDING WINDOW

Also available with nailing fin



STANDARD FEATURES

- Multi-cavity vinyl lineals improve thermal performance and enhance sound absorbency
- Insulating glass provides energy saving thermal efficiency
- Fusion welded frame and sash minimizes air and water infiltration and enhances overall durability
- Sweep lock helps provide a weather-tight seal and added security
- Removable operable sash includes full length interlock and bottom weather reflector
- Dual screw boss, metal reinforced meeting rail provides added strength
- Custom sized to the nearest 1/8"
- Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy saving comfort inside
- Versatile half screen* installed from the inside or outside
- Built-in accessory channels accommodate multiple installation options
- DP-25 Rating (window size tested 72" x 48")
- Jamb depth: 2.625"
- **Limited lifetime warranty**

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids
- Custom sizes available

COLOR OPTIONS**



with an 12 1/2" minimum height for use in a basement opening



Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.

* Screens are not meant to restrain a child from falling through an open window.
** Printing process may affect color shown. Please refer to actual window sample when selecting colors.

