



SERIES 3100 SINGLE HUNG WINDOW

Also available in 2- and 3-lite sliders and picture windows



STANDARD FEATURES

- Bottom sash tilts in for easy cleaning
- Insulated glass panels with optimum thermal air space featuring a warm edge spacer system
- Aluminum-reinforced lock and meeting rails enhance structural integrity
- Double sash locks provide extra security (2 locks standard at 27 1/4" or wider)
- Block and tackle balance system keeps lower sash stationary when opened to any position
- Beveled exterior frame makes a stylish design statement
- Integrated slim-line lift rail allows you to easily operate sash
- Factory applied wrap-around foam enhances thermal efficiency around the frame's exterior
- Factory applied wrap-around foam
- Fusion-welded frame and sash corners ensure frame durability
- Sloped sill accommodates easy water run-off
- Factory-installed half screen standard*
- Head expander and sill angle are included
- Jamb depth: 2.624"
- **Transferable, limited lifetime warranty**

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids
- Custom sizes cut on 1/8" width and height
- Factory mulling of twins, triples and architectural shapes
- Obscure glass
- Double strength glass
- Charcoal aluminum, mesh screen*
- Lifetime glass breakage warranty
- Lifetime labor warranty



COLOR OPTIONS**



Factory applied wrap-around foam



Attractive beveled edge adds classic charm



5/8" or 3/4" flat and 5/8" or 1" contoured grids are available



ENERGY STAR compliance available in all series. Verify product specifics before ordering.

* Screens are not meant to restrain a child from falling through an open window.
** Printing process may affect color shown. Please refer to actual window sample when selecting colors.

