

SERIES 3100 SLIDING WINDOW

Also available in single hung and picture windows




STANDARD FEATURES

- Insulated glass panels with optimum thermal air space featuring a warm edge spacer system
- Aluminum-reinforced lock and meeting rails enhance structural integrity
- Tandem rollers ride easily along friction free glide channel
- Integrated glide rail for easy sash opening and closing
- Available in 1/4 - 1/2 - 1/4 or 1/3 - 1/3 - 1/3 configurations
- XO or OX 2-lite styles available
- Double sash locks provide extra security (2 locks standard at 27 1/4" or higher)
- Beveled exterior frame makes a stylish design statement
- Factory applied wrap-around foam enhances thermal efficiency around the frame's exterior
- Fusion-welded frame and sash corners ensure frame durability
- Factory-installed half screen standard*
- Head expander and sill angle are included
- Jamb depth: 2.75"
- Transferable, limited lifetime warranty

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat grids
- Custom sizes cut on 1/8" width and height
- Factory mulling of twins, triples and architectural shapes
- Obscure glass
- Double strength glass
- Charcoal aluminum, mesh screen*
- Lifetime glass breakage warranty
- Lifetime labor warranty

COLOR OPTIONS**



5/8" or 3/4" flat and 5/8" or 1" contoured grids are available



2-lite sliding window



3-lite sliding window



Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.

* Screens are not meant to restrain a child from falling through an open window.
** Printing process may affect color shown. Please refer to actual window sample when selecting colors.