



# SERIES 3201 DOUBLE HUNG WINDOW

Also available in 2- and 3-lite sliders and picture windows



## STANDARD FEATURES

- Sashes tilt in for easy cleaning
- Reinforced multi-cavity construction offers additional thermal protection and structural integrity
- Positive-action cam lock enhances safety (2 locks standard at 27 1/4" or wider)
- Insulated glass panels with optimum thermal air space featuring a warm-edge spacer system
- Half screen comes standard\*
- Integrated slim-line lift rail allows you to easily operate sash
- Sloped sill reduces air infiltration and accommodates easy water run-off
- Fusion-welded sashes and frame add strength and additional insulation
- Constant force coil balance permits easy sash movement
- Dual push-button night latches provide easy, secure ventilation
- Interlocking sashes help block out drafts
- Dual-fin weather stripping helps reduce air infiltration
- Rubber bulb seal helps block air infiltration
- Jamb depth: 3.25
- Transferable, limited lifetime warranty



Night latch allows for optimum ventilation



Attractive beveled edge adds classic charm



5/8" or 3/4" flat and 5/8" or 1" contoured grids are available

## CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- InsulKor™ multi-cavity foam filled frame injections
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids
- Integrated nail fin (available on double hung, picture window and special shapes)
- Nine exterior painted colors (white interior only)
- Obscure glass
- Double strength glass
- Charcoal aluminum, Clear View, Heavy Duty and FLEXSCREEN® screens\*
- Factory mulling of twins, triples and architectural shapes
- Lifetime glass breakage warranty
- Lifetime labor warranty

### COLOR OPTIONS\*\*



### EXTERIOR PAINTED COLOR OPTIONS\*\*\* (with white interior only)



### EXTERIOR LAMINATE COLOR OPTION\*\* (with white interior only)



Scan to watch a video about the RELIABILT Series 3201.



ENERGY STAR compliance available in all series. Verify product specifics before ordering.

\* Screens are not meant to restrain a child from falling through an open window.  
 \*\* Printing process may affect color shown. Please refer to actual window sample when selecting colors.  
 \*\*\* Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

