

## **SERIES 3201 SLIDING WINDOW**

Also available in double hung and picture windows



## **STANDARD FEATURES**

- Reinforced multi-cavity construction offers additional thermal protection and structural integrity
- Positive-action cam lock enhances safety (2 locks standard at 27 1/4" or wider)
- Insulated glass panels with optimum thermal air space featuring a warm-edge spacer system
- Tandom rollers ride easily along friction free glide channel
- Integrated glide rail for easy sash opening and closing
- Available in 1/4 1/2 1/4 or 1/3 - 1/3 - 1/3 configurations
- XO or OX 2-lite styles available
- Half screen comes standard\*
- Interlocking sashes help block out drafts
- Fusion-welded sashes and frame add strength and additional insulation
- Dual-fin weather stripping helps reduce air infiltration
- Jamb depth: 3.25"
- Transferable, limited lifetime warrantv



5/8" or 3/4" flat and 5/8" or 1" contoured grids are available

## **CUSTOM OPTIONS**

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- InsulKor<sup>™</sup> multi-cavity foam filled frame injections
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids
- Nine exterior painted colors (white interior only)
- Obscure glass
- Double strength glass
- Charcoal aluminum, Clear View, Heavy Duty and FLEXSCREEN® screens\*
- Lifetime glass breakage warranty
- Lifetime labor warranty

COLOR OPTIONS\*\*



Brick Red

Tan Gray Bronze Black EXTERIOR LAMINATE COLOR OPTION\*\* (with white interior only)



Note: Black laminate is only available with nail fin Available grid option is 5/8" contoured grid only.



2-lite sliding window



3-lite sliding window







Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.

Screens are not meant to restrain a child from falling through an open window

Printing process may affect color shown. Please refer to actual window sample when selecting colors.
"Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.





Manufacturer reserves the right to substitute components as necessary for continued product improvement. ENERCY STAR is a registered trademark of the U.S. Department of Energy. ©2023 Lowe's. LOWE'S, Gable Mansard Design, and RELIABILT are registered trademarks of LF, LLC. All are used with permission.