



# SERIES 3500 SLIDING WINDOW

Also available in double hung and picture windows



## STANDARD FEATURES

- Aluminum-reinforced, multicavity construction for thermal performance and structural integrity
- Fusion-welded sashes and frame add strength and additional insulation
- Low-E glass and insulating argon gas enhance thermal efficiency
- DP-30 Rating (window size tested 72" x 48")
- Tandem rollers ride easily along friction free glide channel
- Integrated glide rail for easy sash opening and closing
- Available in 1/4 - 1/2 - 1/4 or 1/3 - 1/3 - 1/3 configurations
- 2-lite available in XX configuration (both sashes operate)
- Rounded sashes create a more elegant finish to complement the interior of your home
- Dual-fin weather stripping helps reduce air infiltration
- Beveled mainframe offers a stylish exterior appearance
- Interlocking sashes help block out drafts
- Positive-action deluxe cam lock provides optimal security (2 locks standard at 27 1/4" or higher)
- Half screen comes standard\*
- Rubber bulb seal helps block air infiltration
- Jamb depth: 3.25"
- Transferable, limited lifetime warranty
- 25 year glass breakage warranty

## CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance grids
- Obscure glass
- Double strength glass
- Charcoal aluminum, Clear View, Heavy Duty and **FLEXSCREEN**® screens\*
- Lifetime glass breakage warranty
- Lifetime labor warranty

### COLOR OPTIONS\*\*



### LAMINATE COLOR OPTION\*\* (with white interior only)



5/8" or 3/4" flat and 5/8" or 1" contoured grids are available



2-lite sliding window



3-lite sliding window



Scan to watch a video about the ReliaBilt Series 3500.



Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.

