



SERIES 3900 SLIDING WINDOW

Also available in double hung and picture windows



STANDARD FEATURES

- Exclusive InsulKor™ polyurethane fiberglass-enriched sash reinforcement for superior thermal and structural performance
- Fusion-welded sashes and frame add strength and boost insulation
- DP-50 Rating (window size tested 72" x 48")
- Beveled mainframe offers a stylish exterior appearance
- Integrated glide channel for easy sash opening and closing
- Tandem rollers ride easily along friction-free glide channel
- 2-lite available in XX configuration (both sashes operate)
- 3-lite available in 1/4 - 1/2 - 1/4 or 1/3 - 1/3 - 1/3 configurations
- 4 1/4" frame thickness enhances appearance and structural integrity
- External accessory groove accommodates nail fin option
- Half screen is standard and removable from the inside*
- Dual low profile, positive-action cam locks increase security (2 locks standard at 27 1/4" width or wider)
- Full interlocking lock and meeting rail
- Full vinyl sash dam on sill and high-performance weather stripping protect against air infiltration
- Jamb depth: 3.25"
- Transferable, limited lifetime warranty
- Lifetime glass breakage warranty

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- Triple-pane, R-5 compliant glass panels
- InsulKor™ multi-cavity foam filled frame injections
- Nail fin accessory for use in remodeling or new construction applications
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance, 1 1/8" Simulated Divided Lite (SDL) grids
- Obscure glass
- Double strength glass
- Charcoal aluminum, Clear View, Heavy Duty and **FLEXSCREEN®** screens*
- Lifetime labor warranty

COLOR OPTIONS**



White

Almond

EXTERIOR PAINTED COLOR OPTIONS** (with white interior only)



Hunter Green

Dark Chocolate

Terrazone

Clay

Brick Red



Gray

Bronze

Tan

Black

INTERIOR LAMINATE OPTIONS** (with white exterior only)



Light Oak

Dark Oak

Cherry

LOCK COLOR OPTIONS**



White

Almond

Dark Chocolate

Cherry

Brass

Brushed Nickel



2-lite sliding window



3-lite sliding window



Optional
InsulKor™
Technology



Scan to watch
a video about
the ReliaBilt
Series 3900.



Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.

*Screens are not meant to restrain a child from falling through an open window.

** Printing process may affect color shown. Please refer to actual window sample when selecting colors.

*** Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.

