

## SERIES 450 DOUBLE HUNG WINDOW

Also available in 2- and 3-lite sliders and picture windows



## STANDARD FEATURES

- Beautiful, true brick mould exterior frame perimeter
- Bottom sash tilts in for easy cleaning
- Fully welded frame and sash corners
- Sloped sill for easy water run-off
- Insulated glass panels with optimum thermal air space featuring warm-edge spacer system
- DP-35 Rating (window size tested 36" x 74") (available with DP-50 option)
- Series 455/465 available with DP-50 Rating
- Integrated J-channel (Series 460 available without J-channel)
- Pre-punched nail fin makes installation simple
- Block and tackle balance system
- Continuous head and sill on twins and triples
- Half screen comes standard\*
- Jamb depth: 3.868"
- Limited lifetime warranty



Brick mould exterior

3 1/4" flat casing

nose

nailing with bull fins and integrated J-channel

Pre-punched Optional wood jamb extension and factory mull for simpler installation

## Screens are not meant to restrain a child from falling through an open window

Printing process may affect color shown. Please refer to actual window sample when selecting colors.
"Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.



- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance, 1 1/8" Simulated Divided Lite (SDL) grids
- Nine exterior painted colors (white interior only)
- Exterior 3 1/4" flat casing with Sill Nose
- Dual push-button night vents for secure ventilation
- Brass or brushed nickel locks
- Factory mulling of twins, triples and architectural shapes
- Paintable or stainable wood jamb extensions (4 9/16" and 6 9/16")
- Charcoal aluminum mesh screen\*
- Custom sizes available



EXTERIOR PAINTED COLOR OPTIONS\*\*\*







Features a Low Profile Lock





Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.





