

SERIES 700 CASEMENT WINDOW

Also available in Series 705 awning window



STANDARD FEATURES

- Beautiful beveled exterior frame perimeter
- Low profile handle folds in and provides a popular aesthetic appeal
- Narrow profile permits expanded viewing area
- Fusion-welded frame and sash for weather-tight performance
- Full-perimeter double weather stripping
- Insulated glass panels featuring warm-edge spacer system
- Casement windows open 90 degrees for better ventilation
- Full screens mount on the interior and are removable*
- Tandem locks standard on all casements over 34" in height
- Standard colors are white or almond
- Jamb depth: 3.25"
- Transferable, limited lifetime warranty
- Lifetime glass breakage warranty



Sleek folding handle



Attractive beveled edge adds classic charm



5/8" or 3/4" flat and 5/8" or 1' contoured grids are available

CUSTOM OPTIONS

- Low-E Glass
- Low-E Glass with Argon Gas
- Ultra Low-E Glass with Argon Gas
- 5/8" or 1" contoured, 5/8" or 3/4" flat, 5/8" contoured valance and 1/8" simulated divided lite (SDL) grids
- Obscure strength glass
- Double strength glass
- Brass or brushed nickel locks
- 2" simulated meeting rail
- Exterior painted colors and decorative hardware available
- Charcoal aluminum, Clear View and heavy duty screens*
- Custom sizes available





EXTERIOR LAMINATE OPTION** (with white interior only)



EXTERIOR PAINTED COLOR OPTIONS***
(with white interior only)















Single vent casement



Single vent awning





Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.





Screens are not meant to restrain a child from falling through an open window

[&]quot;Printing process may affect color shown. Please refer to actual window sample when selecting colors.
"Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. See full cleaning instructions for details.