



RELIABILT SERIES 83 AND 85 ALUMINUM WINDOWS AND PATIO DOORS

Product	Window Type	Series/Model #	RELIABILT Series/Model #	Test Size	Rating	Reinforcement	Air Infiltration (cfm/sq. ft)	Water Pressure (psf)	Structural Pressure (psf)	Florida Approval	TDI Approval	Test Report Number	Specification Type
Fixed	Standard	4701F	Reliablilt 83 Series	72 x 96	F-R50		0.01	7.50	+50/-50	15301	WIN-987	11150-1	Standard-AAMA 101
Fixed	Standard	4701FL	Reliablilt 83 Series	53 x 72	F-R50		0.02	7.50	+50/-50	14253	N/A	10389-1	Standard-AAMA 101
Fixed	Standard	4701FIR	Reliablilt 83 Series	53 x 74	R-PG40		0.10	6.00	+50/-57	15301	FL 15301	08-087	IMP-Missile D, Wind Zone 3
Fixed	Standard	4701FLIR	Reliablilt 83 Series	53 x 74	R-PG40			6.0	+50/57	15301	FL 15301	08-088	IMP-Missile D, Wind Zone 3
Fixed	Standard	4701FL	Reliablilt 83 Series	72 x 96	LC-PG40		0.10	7.50	+40/-40	14434	WIN-987	12325-1	Standard-AAMA 101
Fixed	Standard	4701FL	Reliablilt 83 Series	72 x 72	FW-LC55		0.01	12.00	+55/-55	14434	WIN-987	13668-1	Standard-AAMA 101
Fixed	Standard	4701FLHV	Reliablilt 83 Series	52.125 x 71	R-PG50		0.01	7.50	+50/-50	14434	N/A	J2927.01	HVHZ Non-Impact
Fixed	Standard	4701FLHV	Reliablilt 83 Series	52.125 x 71	R-PG50		0.02	7.50	+50/-50	14434	N/A	J8133.01-550-18	HVHZ Non-Impact
Horizontal Slider	Standard	4720	Reliablilt 83 Series	72 x 48	HS-R50		0.18	7.50	+50/-67	14251	WIN-990	10177-1	Standard-AAMA 101
Horizontal Slider	Standard	4720	Reliablilt 83 Series	119.25 x 59.25	HS-R30		0.18	7.50	+30/-30	14251	WIN-990	10125-1	Standard-AAMA 101
Horizontal Slider	Standard	4720FIR	Reliablilt 83 Series	72 x 47	HS-R50		0.18	7.50	+50/-66	N/A	N/A	06-088	IMP-Missile D, Wind Zone 3
Horizontal Slider	Standard	4720	Reliablilt 83 Series	74 x 63	HS-R35		0.21	5.25	+35/-45	14251	WIN-990	07-223	Standard-AAMA 101
Horizontal Slider	Standard	4720FL	Reliablilt 83 Series	74 x 63	HS-R35		0.26	5.25	+35/-40	N/A	N/A	07-222	Standard-AAMA 101
Horizontal Slider	Standard	4720FL	Reliablilt 83 Series	72 x 72	HS-LC35		0.04	5.25	+35/-35	14028	N/A	13234-1	Standard-AAMA 101
Single Hung	Standard	4712FLHV	Reliablilt 83 Series	52.125 x 71	R-PG50		0.07	7.50	+50/-50		N/A	19308.01	HVHZ Non-Impact
Single Hung	Standard	4710F	Reliablilt 83 Series	53 x 72	R-PG40		0.18	6.00	+45/-60	N/A	WIN-986	12055-2	Standard-AAMA 101
Single Hung	Standard	4710F	Reliablilt 83 Series	48 x 84	H-R40		0.11	6.00	+50/-60	N/A	WIN-986	12055-3	Standard-AAMA 101
Single Hung	Standard	4712FL	Reliablilt 83 Series	48 x 84	LC-PG50		0.16	7.50	+50/-70	14039	N/A	13259-2	Standard-AAMA 101
Single Hung	Standard	4712FL	Reliablilt 83 Series	53 x 72	H-R50		0.11	7.50	+50/-60	14039	N/A	13262-1	Standard-AAMA 101
Single Hung	Standard	4712F	Reliablilt 83 Series	53 x 72	H-R50		0.19	7.50	+50/-60	14039	WIN-1396	13262-2	Standard-AAMA 101
Single Hung	Standard	4712F	Reliablilt 83 Series	48 x 84	H-LC50		0.10	7.50	+50/-60	14039	WIN-1396	13259-1	Standard-AAMA 101
Single Hung	Standard	4712FIR	Reliablilt 83 Series	48 x 84	H-LC50		0.10	7.50	+50/-57	15329	WIN-1415	13482-1	IMP-Missile D, Wind Zone 3
Single Hung	Standard	4712F, 4712FLIR	Reliablilt 83 Series	53 x 72	H-R50		0.20	7.50	+50/-57	15329	WIN-1415	13420-1	IMP-Missile D, Wind Zone 3
Single Hung	Standard	4712FLHV	Reliablilt 83 Series	52.125 x 71	R-PG50		0.03	7.52	+50/-50	15329	N/A	J2927.02	HVHZ Non-Impact
Single Hung	Standard	4712FLHV	Reliablilt 83 Series	52.125 x 71	R-PG50		0.03	7.52	+50/-50	15329	N/A	J8133.02	HVHZ Non-Impact
Sliding Door	Standard	4780	Reliablilt 83 Series	192 x 96	SGD-R30		0.22	5.25	+30/-30	14634	N/A	11212-1	Standard-AAMA 101
Sliding Door	Standard	4780	Reliablilt 83 Series	192 x 96	SGD-R35		0.22	5.25	+35/-35	14634	N/A	11276-1	Standard-AAMA 101
Sliding Door	Standard	4780	Reliablilt 83 Series	96 x 96	SGD-R25		0.21	3.75	+25/-50	14634	N/A	10734-2	Standard-AAMA 101
Sliding Door	Standard	4780	Reliablilt 83 Series	106.25 x 95	SD-LC50		0.24	7.50	+50/-50	14038	DR-473	10-146	Standard-AAMA 101
Sliding Door	Standard	4780	Reliablilt 83 Series	141 X 95	R-PG35		0.24	7.50	+40/-40	14038	DR-473	10-145	Standard-AAMA 101



RELIABILT SERIES 83 AND 85 ALUMINUM WINDOWS AND PATIO DOORS

Product	Window Type	Series/Model #	RELIABILT Series/Model #	Test Size	Rating	Reinforcement	Air Infiltration (cfm/sq. ft)	Water Pressure (psf)	Structural Pressure (psf)	Florida Approval	TDI Approval	Test Report Number	Specification Type
Fixed	Standard	801/805F	Reliablilt 85 Series	71.25 x 59.25	R-PG50		0.02	7.50	+50/-50	N/A	WIN-2524	9813-3	Standard-AAMA 101
Fixed	Standard	801/805F	Reliablilt 85 Series	71.25 x 71.25	R-PG45		0.01	7.50	+45/-45	N/A	WIN-2524	9813-4	Standard-AAMA 101
Horizontal Slider	Standard	4820/4830	Reliablilt 85 Series	119.25 x 59.25	HS-R30		0.15	4.50	+30/-30	N/A	WIN-991	10182-1	Standard-AAMA 101
Single Hung	Standard	4810FIR	Reliablilt 85 Series	47.5 x 71.375	H-R40		0.19	6.00	+50/-50	N/A	N/A	04-229	IMP-Missile D, Wind Zone 3
Single Hung	Standard	4810F	Reliablilt 85 Series	48 x 84	LC-PG40		0.19	6.00	+40/-60	N/A	WIN-1397	12553-1	Standard-AAMA 101
Single Hung	Standard		Reliablilt 85 Series	48 x 96	H-LC40		0.05	6.00	+40/-45	N/A	WIN-1397	12553-2	Standard-AAMA 101
Single Hung	Standard	4812F	Reliablilt 85 Series	48 x 84	H-LC50		0.12	7.50	+50/-60	14039	WIN-1398	13264-1	Standard-AAMA 101
Single Hung	Standard	4812F	Reliablilt 85 Series	48 x 96	H-LC30		0.09	7.50	+30/-30	14039	WIN-1398	13431-1	Standard-AAMA 101
Single Hung	Standard	4712FIR	Reliablilt 85 Series	48 x 84	H-LC50		0.10	7.50	+50/-57	15329	WIN-1415	13482-1	IMP-Missile D, Wind Zone 3
Single Hung	Standard	4712F, 4712FLIR	Reliablilt 85 Series	53 x 72	H-R50		0.20	7.50	+50/-57	15329	WIN-1415	13420-1	IMP-Missile D, Wind Zone 3
Sliding Door	Standard	4880IR	Reliablilt 85 Series	186 x 96	LC-PG70-SD		0.16	10.50	+70/-70	15943	DR-623	12-173	IMP-Missile D, Wind Zone 3
Sliding Door	Standard	4880IR	Reliablilt 85 Series	186 x 96	LC-PG50-SD		0.16	7.50	+50/-70	15943	DR-623	12-173	IMP-Missile D, Wind Zone 3
Sliding Door	Standard	4880	Reliablilt 85 Series	186 x 96	LC-PG50-SD		0.16	7.50	+50/-50	15943	DR-621	12-147	Standard-AAMA 101

TEST REPORTS ARE AVAILABLE UPON REQUEST