

## SERIES 350P SINGLE HUNG WINDOW

Also available in 2- and 3-lite sliders and picture windows



## STANDARD FEATURES

- Nail fin with either a 1" or 1-3/8" setback
- A baffled weep system prevents insect intrusion, while facilitating rapid rainwater drainage
- Bottom sash is side loaded and removable
- Dual cam-action lock and continuous weatherstripping
- Optional structural warm-edge spacer system for premium performance and structural integrity
- Hardware and fasteners are corrosion resistant for durability
- Durable vinyl and fusion-welded corners
- Designed for durability with a frame depth of 3-7/16 inches
- Design Pressure Rating DP 45
  (window size tested 48 x 84)
- Limited Lifetime Warranty

## **CUSTOM OPTIONS**

- Low-E Glass
- HP Low-E Glass with Argon Gas
- HPMax Triple-Pane Glass
- Title 24 Glass Compliance Standards
- Tinted, obscure, laminated, tempered and single glaze glass
- Frame options include Block Frame, Dual Wall Flush Fin Nailing Fin, J-Channel, Stucco Key
- Factory mulling of twins, triples and architectural shapes
- Color-coordinated grids between-the-glass (GBG) in flat 5/8", sculptured 5/8" or 1" styles; simulated-divided-lite (SDL) 7/8" or 1-1/4" styles; 2" accent bar
- Auto Lock feature provides added security
- 3 vinyl color options and 2 co-extruded exterior colors
- Custom sizes available

Prairie

Double Prairie

Perimeter Prairie

WINDOW GRID PATTERNS





WINDOW HARDWARE FINISHES\*



CO-EXTRUDED COLOR OPTIONS\*\* (exterior)



- Black Ext Black Int RELIABILT'S dark exterior colors are engineered specifically to satisfy the
- design and performance requirements of the western region. Through the co-extrusion process, both the interior and exterior colors are fused into the window profile. This produces a long-lasting, high-performance color that is an integral part of the window, and not just a coating on the exterior surface.

\* Printing process may affect color shown. Please refer to actual window sample when selecting colors. \*\* Laminated black interior with co-extruded black exterior on windows. Geographically limited availability.





Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.



Manufacturer reserves the right to substitute components as necessary for continued product improvement. ENERCY STAR is a registered trademark of the U.S. Department of Energy. ©2024 Lowe's. LOWE'S, Gable Mansard Design, and RELIABILT are registered trademarks of LF, LLC. All are used with permission.