

SERIES 350P HORIZONTAL SLIDING WINDOW





STANDARD FEATURES

- Nail fin with either a 1" or 1-3/8" setback
- A baffled weep system prevents insect intrusion, while facilitating rapid rainwater drainage
- Removable sash and limited sash stop
- For safe ventilation, sliding windows incorporate an optional vent system
- Adjustable rollers are wide for hassle-free operation
- Dual cam-action lock and continuous weatherstripping
- Optional structural warm-edge spacer system for premium performance and structural integrity
- Hardware and fasteners are corrosion resistant for durability
- Durable vinyl and fusion-welded corners
- Designed for durability with a frame depth of 3-7/16 inches
- Design Pressure Rating DP 40 (window size tested 60 x 48)
- Limited Lifetime Warranty

VINYL COLOR OPTIONS* (interior & exterior)





WINDOW HARDWARE FINISHES*



CO-EXTRUDED COLOR OPTIONS** (exterior)







CUSTOM OPTIONS

- Low-E Glass
- HP Low-E Glass with Argon Gas
- HPMax Triple-Pane Glass
- Title 24 Glass Compliance Standards
- Tinted, obscure, laminated, tempered, single glaze glass
- Frame options include Block Frame, Dual Wall Flush Fin Nailing Fin, J-Channel, Stucco Key
- Factory mulling of twins, triples and architectural shapes
- Color-coordinated grids between-the-glass (GBG) in flat 5/8", sculptured 5/8" or 1" styles; simulateddivided-lite (SDL) 7/8" or 1-1/4" styles; 2" accent bar
- Auto Lock feature provides added security
- 3 vinyl color options and 2 co-extruded exterior colors
- Custom sizes available





















Many RELIABILT products can be configured to meet ENERGY STAR® ratings in most climate zones. Verify product specifics before ordering.



